



Art. no. **4200**

High pressure grease control gun, steel body, inlet connection 1/4" BSP (M), outlet connection M 10x1.

Art. no. **4201**

High pressure grease control gun art.no. 4200, but additionally equipped with a trigger guard.



Art. no. **4205**

High pressure grease control gun with 300 mm – steel braid rubber outlet hose ø ext. 10 mm and 4 - jaws - hydraulic coupler.

Art. no. **4206**

High pressure grease control gun art.no. 4205, but additionally equipped with a trigger guard.



Art. no. **4208**

High pressure grease control gun with rigid outlet pipe and 4 - jaws – hydraulic coupler.

Art. no. **4207**

High pressure grease control gun art.no. 4208, but additionally equipped with a trigger guard.



Art. no. **4209**

High delivery grease control gun for the transfer of grease, with rigid outlet, ø 20 mm. Working pressure up to 200 bar, burst pressure 350 bar.

Art. no. **4204**

Grease control gun for the transfer of grease, with rigid outlet, ø 16 mm. Working pressure up to 180 bar, burst pressure 320 bar.



Art. no. **4221**

High pressure rotating "Z" – swivel, connections 1/4" BSP (M – F). For the installation between hose and control gun. Allows a complete 360° - rotation on the 3 axes, also under pressure.

Art. no. **4228**

Straight high pressure rotating swivel, connections 1/4" BSP (M – F). For the installation between hose and control gun. Allows a complete 360° - rotation on the 1 axe, also under pressure.